



STATEMENT OF ACCEPTANCE OF AN ADHESIVE/BONDING PASTE

Certificate No. MATS/4810/1

This certificate is issued to the company named below. Based on examination of the data submitted the product described is considered acceptable for use in constructions built under Lloyd's Register's survey. This acceptance is subject to Lloyd's Register being informed of any changes in or modifications to the product and the product being used in accordance with the manufacturer's instructions and with the relevant requirements of Lloyd's Register's Rules and Regulations.

Company	NORD COMPOSITES CONDE FOLIE FRANCE
Trade name	NORCOL CD 792 RC
Type	Vinylester
Application	Bonding FRP substrates
Data submitted	Technical data, witnessed test data, Surveyor site inspection report Norcol 792 RC: mean lap shear strength (ambient temperature) 4.9MPa Norcol 792 RC: mean lap shear strength (aged 28 days in sea water at 35°C) 4.8MPa Norcol 792 RC LGT: mean lap shear strength (ambient temperature) 3.8MPa Norcol 792 RC LGT: mean lap shear strength (aged 28 days in sea water at 35°C) 3.1MPa
Applicable LR Rules	Rules and Regulations for Classification of Special Service Craft (i) The manufacturer's recommendations for surface preparation and cure conditions must be followed (ii) Users should ensure tests are carried out to establish the suitability of the products for the bonding of their particular substrates
Valid until	29 July 2021
Date	29 July 2016

M Jorgia

Lead Specialist to Lloyd's Register EMEA
A member of the Lloyd's Register group