

Material Safety Data Sheet
According to 2001/58/EC



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 **Version :** 1.0.0
Release Date : 21.01.2015

page : 1 / 7

1 Identification of substance

Trade name

ICOM MC Resin GR 1110 NS

Application of the substance / the preparation

Casting Resin.

Manufacturer/Supplier:

ICOM Composites A/S

Street/Po. box

Birkedam 10 C/7

Nationality/zip code/town

DK - 6000 Kolding

Telephone / Fax

+45 75 50 62 22 / +45 75 50 62 23

2 Composition/Data on components:


- **Chemical characterization**
- **Description:** Orthophthalate Polyester Resin For Polymer Concrete
- **Dangerous components**

CAS: 100-42-5	Styrene	35 ± 2%
EINECS: 202-851-5	Xn; R 10-20-36/38	

- **Additional information** For the wording of the listed risk phrases refer to section 16.

3 Hazard identification

- **Hazard designation:**



Xn Harmful

- **Information pertaining to particular dangers for man and environment**

R10 Flammable.
R11 Highly Flammable
R36/38 Irritating to eyes and skin
R43 May cause sensitization by skin contact.

- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 **Version :** 1.0.0
Release Date : 21.01.2015

page : 2 / 7

4 First aid measures

- **General information**
Take affected persons into the open air.
Personal protection for the First Aider.
- **After inhalation**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persists. In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact** *instantly wash with water and soap and rinse thoroughly.*
- **After eye contact** *rinse opened eye for several minutes under running water. Then consult doctor.*
- **After swallowing**
Rinse mouth with water.
Seek medical treatment.

5 Fire fighting measures

- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** *Water with a full water jet.*
- **Protective equipment:**
Water breathing apparatus.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Person-related safety precautions:**
Use breathing protection against the effects of fumes/dust/aerosol.
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents.

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Keep containers tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 **Version :** 1.0.0
Release Date : 21.01.2015

page : 3 / 7
(Contd. from page 2)

- **Information about protection against explosions and fires:** keep ignition sources away – Do not smoke.
- **Storage**
- **Requirements to be met by storerooms and containers:** no special requirements.
- **Information in storage in one common storage facility:**
Store away from oxidizing agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Components with critical values that require monitoring at the workplace:**
100-42-5 Styrene

MEL (Great Britain) Short-term value: 1080mg/m³, 250ppm
Long-term value: 430 mg/m³, 100ppm
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **Personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures should be adhered to in handling the chemicals.
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled impregnated garments.
Wash hands during breaks and at the end of the work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Use breathing protection in case of insufficient ventilation.
In case of short term exposition use breathing apparatus; in case of intensive or continuous exposition use breathing apparatus with independent air supply.
Filter A
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/substance/preparation.
Check the permeability prior to each renewed use of the glove.
- **Material of gloves**
Fluorocarbon rubber (Viton)
PVA gloves
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Not suitable are gloves made of the following materials:**
Nitrile rubber, NBR
Natural rubber, NR
PVC gloves
Neoprene gloves



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 Version : 1.0.0
Release Date : 21.01.2015

page : 4 / 7

- **Eye protection:** *Tightly sealed safety glasses.*
- **Body protection:** *Protective work clothing.*

(Contd. from page 3)

9 Physical and chemical properties:

- **General Information**
 - Form:** liquid
 - Colour:** clear pale yellow
 - Odour:** characteristic
- **Change in condition**
 - Melting point/Meeting range:** not determined
 - Boiling point/Boiling range:** 145°C
- **Flash point:** 32 °C (DIN 53213)
- **Ignition temperature:** 480 °C (DIN 51794)
- **Self-inflammability;** *Product is not self-inflammable.*
- **Danger of explosion:** *Product is not explosive. However, formation of explosive air/vapor mixtures is possible.*
- **Critical values for explosion:**
 - Lower:** 1.2 Vol %
 - Upper:** 8.9 Vol %
- **Vapour pressure at 20°C:** 7hPa
- **Density at 25°C:** 1.12 ± 0.01 g/cm³
- **Solubility in / Miscibility with Water:** *insoluble*
- **pH-Value:** *not applicable*
- **Viscosity:**
 - dynamic at 25°C:** 800 – 1200 mPa S

10 Stability and reactivity

- **Conditions to be avoided:** *No decomposition if used and stored according to specifications.*
- **Dangerous reactions:**
 - Reacts with peroxides and other radical forming substances*
 - Exothermic polymerization*
- **Dangerous products of composition:**
 - In case of fire:*
 - carbon monoxide and carbon dioxide*



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 **Version :** 1.0.0
Release Date : 21.01.2015

page : 5 / 7

11 Toxicological information

- **Acute toxicity**
LD/LC50 values those are relevant for classification:

100-42-5 Styrene

Oral	LD50	5000mg/kg (rat)
Inhalative	LC50 (4 th)	24 mg/l (rat)

- **Primary irritant effect:**
- *Primary irritant for skin and mucous membranes.*
- **on the skin:** Irritant for skin and mucous membranes.
- **on the eye:** Irritant effect.
- **Sensitization:** No sensitizing effect known.

12 Ecological information:

- **Information about elimination (persistence and degradability)**

100-42-5 Styrene

OECD 301C-Test > 60% (Literature)

- **Behavior in environmental systems:**
- **Mobility and bioaccumulation potential:**

100-42-5 Styrene

BCF 13.5 – 64 (Literature)

Log Pow 3.16 (Literature)

- **Ecotoxicological effects:**
- **Acquatic toxicity:**

100-42-5 Styrene

LC50 (48h) 23mg/l (*Daphnia magna*)

LC50 (96h) 32 mg/l (*pimephales promelas*)

- **General notes:** Water hazard class 2 (self-assessment): hazardous for water.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES
07 02 00 waste from the MFSU of plastics, synthetic rubber and ma-made fibres
07 02 99 wastes not otherwise specified
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 Version : 1.0.0
Release Date : 21.01.2015


page : 6 / 7

14 Transport information

- Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)
 - ADR/RID-GGVS/E Class: 3 Flammable liquids.
 - Kemler Number: 30
 - UN-Number: 1866
 - Packaging group: III
 - Label: 3
- Designation of goods: 1866 RESIN SOLUTION, Special provision 640E
- Maritime transport IMDG/GGVSea:
 - IMDG/GGVSea Class: 3
 - UN-Number: 1866
 - Label: 3
 - Packaging group: III
 - EmS Number: F-E, S-E
 - Marine pollutant: No
 - Proper shipping name: RESIN SOLUTION
- Air transport ICAO-TI and IATA-DGR:
 - ICAO/IATA Class: 3
 - UN/ID Number: 1866
 - Label: 3
 - Packaging group: III
 - Proper shipping name: RESIN SOLUTION

15 Regulatory information

- Classification according to EC-regulations:
The product has been classified and labeled in accordance with EC Directives.
- Code letter and hazard designation of product:



Xn Harmful

- Hazard-determining components of labeling:
Styrene
- Risk phrases:
 - 10 Flammable.
 - 20 Harmful by inhalation.
 - 36/38 Irritating to eyes and skin.
 - 43 May cause sensitization by skin contact
- Safety phrases:
 - /9 keep container in a well-ventilated place.
 - /23 Do not breathe fumes/aerosol.
 - /26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 - 36/37 Wear suitable protective clothing and gloves.
 - /43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
 - /60 This material and its container must be disposed of as hazardous waste.

Material Safety Data Sheet
According to 2001/58/EC



Tradename : ICOM MC Resin GR 1110 NS
Updated : 15.10.2011 **Version :** 1.0.0
Release Date : 21.01.2015

page : 7 / 7
(Contd. from page 6)

- **Natural regulations**
- **Water hazard class:** Water hazard class 2 (elf-assessment): hazardous for water.

16 Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
 - 10 Flammable.
 - 20 Harmful by inhalation.
 - 36/38 Irritating to eyes and skin.
 - 43 May cause sensitization by skin contact
- **Department issuing data specification sheet:** Product Safety Division – Navi Mumbai, INDIA
- **Contact:**
Product Safety Division – Navi Mumbai, INDIA
Tel: + 91-22-27682720
Fax: +91-22-27682721
E-mail: mechemcoresins@vsnl.net