

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : NORCOL 303 RC PRE_ACCELERATED
Product code : CD303RC
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : POLYESTER BONDING PASTE

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Nord Composites
Z.A. Route d'Amiens
F-80890 Condé-Folie - France
T 33 3 22 31 57 57 - F 33 3 22 31 86 97
qualite@nord-composites.com - www.nord-composites.com

1.4. Emergency telephone number

Emergency number : ORFILA - 0033 1 45 42 59 59

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Repeated exposure, Category 1	H372

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : Styrene

Hazard statements (CLP) : H226 - Flammable liquid and vapour
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H361 - Suspected of damaging fertility or the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (CLP) : P280 - Wear protective gloves, protective clothing, eye protection
P241 - Use explosion-proof electrical equipment
P271 - Use only outdoors or in a well-ventilated area
P370+P378 - In case of fire: Use Water fog, foam, extinguishing powder, carbon dioxide (CO2)

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

EUH-statements : for extinction
P264 - Wash hands thoroughly after handling
P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking
: EUH208 - Contains CAS 136-52-7. May produce an allergic reaction

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Styrene (Note D)	(CAS No) 100-42-5 (EC no) 202-851-5 (EC index no) 601-026-00-0 (REACH-no) 01-2119457861-32	20 - 30	Repr.Cat.3; R63 Xn; R20 Xn; R48/20 Xi; R36/38 R10	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
(Note P)	(CAS No) 64742-95-6 (EC no) 265-199-0 (EC index no) 649-356-00-4 (REACH-no) 01-2119455851-35	< 1	Xn; R65 N; R51/53 R10 R67 R66 Xi; R37	Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethanediol, ethylene glycol substance with a Community workplace exposure limit	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1 (REACH-no) 01-2119472426-35	< 1	Xn; R22	Acute Tox. 4 (Oral), H302
Cobalt bis(2-ethylhexanoate)	(CAS No) 136-52-7 (EC no) 205-250-6 (REACH-no) 01-2119524678-29	< 1	Repr.Cat.3; R62 R43 N; R50/53	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Specific concentration limits:

Name	Product identifier	Specific concentration limits: DSD/DPD	Specific concentration limits: CLP
Styrene	(CAS No) 100-42-5 (EC no) 202-851-5 (EC index no) 601-026-00-0 (REACH-no) 01-2119457861-32	(C >= 12,5) Xn;R20 (C >= 12,5) Xi;R36/38	

Note D : Certaines substances susceptibles de se polymériser ou de se décomposer spontanément sont généralement mises sur le marché sous une forme stabilisée. C'est sous cette forme qu'elles figurent dans la troisième partie. Cependant, de telles substances sont parfois mises sur le marché sous forme non stabilisée. Dans de tels cas, le fournisseur doit faire figurer sur l'étiquette le nom de la substance, suivi de la mention «non stabilisé(e)».

Note P : La classification comme cancérogène ou mutagène peut ne pas s'appliquer s'il peut être établi que la substance contient moins de 0,1 % poids/poids de benzène (no EINECS 200-753-7). Si la substance n'est pas classée comme cancérogène, les conseils de prudence (P102)P260-P262-P301 + P310- P331 (tableau 3.1) ou les phrases S (2-)23-24-62 (tableau 3.2) doivent à tout le moins s'appliquer. La présente note ne s'applique qu'à certaines substances complexes dérivées du pétrole, visées dans la troisième partie.

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.



MATERIAL SAFETY SHEET

ICOM 303 RC - PRE ACCELERATED

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Irritation.
Symptoms/injuries after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Use water spray or fog for cooling exposed containers. Prevent entry to sewers and public waters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours. fume.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Styrene (100-42-5)

United Kingdom

WEL STEL (mg/m³)

1080 mg/m³

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

United Kingdom	WEL STEL (ppm)	250 ppm
ethanediol, ethylene glycol (107-21-1)		
EU	IOELV TWA (mg/m ³)	246 mg/m ³

ethanediol, ethylene glycol (107-21-1)		
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	492 mg/m ³
EU	IOELV STEL (ppm)	100 ppm

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : Wear appropriate mask



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: - 31 °C (Styrene)
Freezing point	: No data available
Boiling point	: 145 °C (Styrene)
Flash point	: 31 °C (Styrene)
Auto-ignition temperature	: 490 °C (Styrene)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,31 - 1,35
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.1 %(V) (Styrene) 6.1 %(V) (Styrene)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

Styrene (100-42-5)	
LD50 oral	> 5000 mg/kg
LD50 dermal	> 5000 mg/kg
ethanediol, ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg
LD50 dermal	> 3500 mg/kg mouse
LC50 inhalation rat (mg/l)	> 2,5 mg/l

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure.

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Styrene (100-42-5)	
LC50 fish 1	4,02 mg/l
EC50 Daphnia 1	4,7 mg/l
EC50 72h algae (1)	4,9 mg/l
ethanediol, ethylene glycol (107-21-1)	
LC50 fish 1	72860 mg/l
EC50 Daphnia 1	> 100 mg/l
EC50 96h algae (1)	6500 - 13000 mg/l
NOEC chronic fish	15380 mg/l
NOEC chronic crustacea	8590 mg/l

12.2. Persistence and degradability

ethanediol, ethylene glycol (107-21-1)	
Biodegradation	90 - 100 %

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.




MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

SECTION 14: Transport information


In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA
14.1. UN number		
1866	1866	1866
14.2. UN proper shipping name		
RESIN SOLUTION	RESIN SOLUTION	Resin solution
Transport document description		
UN 1866 RESIN SOLUTION, 3, III, (D/E)	UN 1866 RESIN SOLUTION, 3, III	UN 1866 Resin solution, 3, III
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

14.6. Special precautions for user

- Overland transport

Special provisions (ADR) : 640E
 Transport category (ADR) : 3
 Hazard identification number (Kemler No.) : 30
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : •3YE

- Transport by sea

EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E
 Stowage category (IMDG) : A
 Properties and observations (IMDG) : Miscibility with water depends upon the composition.

- Air transport

PCA packing instructions (IATA) : 355
 CAO packing instructions (IATA) : 366
 ERG code (IATA) : 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
 Contains no substance on the REACH candidate list
 Contains no REACH Annex XIV substances

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H361f	Suspected of damaging fertility
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction
R10	Flammable
R20	Harmful by inhalation
R22	Harmful if swallowed
R36/38	Irritating to eyes and skin
R37	Irritating to respiratory system
R43	May cause sensitisation by skin contact
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

MATERIAL SAFETY SHEET



ICOM 303 RC - PRE ACCELERATED

Flam. Liq. 3	H226	
Acute Tox. 4 (Inhalation:dust,mist)	H332	
Skin Irrit. 2	H315	

Eye Irrit. 2	H319	
Repr. 2	H361	
STOT RE 1	H372	

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product